



产品特性:

- 1, 气味清香, 粘性好, 能适应各种自动加热设备。
- 2, 使用方便, 干燥时间长, 不宜变形, 不发霉, 不起泡。
- 3, 易清洁, 环保。

Product features:

- 1, odour fragrance, good viscosity, can adapt to all kinds of automatic heating equipment.
- 2, easy to use manual production, the drying time is long, non-deformation, non-stale, no bubbles.
- 3, easy to clean, environmental protection.

使用方法:

本品直接放入胶槽中, 加热温度为70-85度, 加热溶解为水状方可使用, 加水比例为5%-10%, 停机时使用热水将涂胶轮清洗干净。

Method of Use:

the product directly into the glue tank, the heating temperature is 70-85 degrees, heating dissolved into water for use, add water 5% - 10%, when stop using hot water will be cleaned of gluing roller.

主要性能指标:

颜色	状态	固含量	粘度	速度	软化点	包装	储存温度	储存期
浅棕色	块状	60 ± 1%	1600 ± 50cps	20-30个/分	40度	25kg/箱	5-28度	6个月

Main Parameter:

Color	Status	Solid Content	Viscosity	Speed	Softening Temperature	Packing	Storage Temperature	Storage Life
Light Yellow	Blocky Structure	60 ± 1%	1600 ± 50cps	20-30 Case/min	40℃	25kg /cartons	5-28℃	6 Months